



LY?MANUFACTURING CO.,LTD.

3HR4085T+[217-3000/1]L THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 3HR4085T+[217-3000/1]L

| | |
|--|----------------|
| Days to Ship | 42 Days |
| Rail Width W1 | 35 mm |
| Mounting Height M | 40 mm |
| Number of blocks | 3 |
| Material | Carbon Steel |
| Rail Length L | 217 ~ 3000 mm |
| Accuracy Grade | Standard Grade |
| Callout Size | 4085 |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 59500 |
| Basic Load Rating Static Rating Co(N) | 91700 |
| Allowable static moment MA(N · m) | 4480 |
| Allowable static moment MB(N · m) | 4480 |
| The outside dimension W of block | 50.4 mm |
| The outside dimension L of block | 215.9 mm |
| Mounting Hole Dimension S(M) | M14 |
| The dimension L1 of bocks | 158.9 mm |
| LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block | Not Provided |

3HR4085T+[217-3000/1]L Bearing 2D drawings and 3D
CAD models



LY?MANUFACTURING CO.,LTD.

| | |
|---|--------------|
| is not available.) | |
| LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.) | Not Provided |