



LY?MANUFACTURING CO.,LTD.

3SRS7WS+[33-300/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 3SRS7WS+[33-300/1]L[H,P]M

Days to Ship	27 Days
Block Type	[Short] S: Short
The number of LM blocks combined with a axis	3
Nominal Part Number	7W
Rail Type	Wide Rail
Rail Width W1	14 mm
Mounting Height M	9 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	1380
Basic Load Rating Static Rating Co(N)	1350
Allowable Static Moment MA(N m)	2.89
Allowable Static Moment MB(N m)	3.32
Allowable Static Moment MC(N m)	9.95
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	25 mm
Block external dimension L	22.5 mm
Number of Block Mounting	2

3SRS7WS+[33-300/1]L[H,P]M Bearing 2D drawings and 3D CAD models



LY?MANUFACTURING CO.,LTD.

Holes(holes)	
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	11.9 mm