



# LY?MANUFACTURING CO.,LTD.

## HSR35A[1,2,3,4,5,6,7,8,9]+[1 23-3000/1]L[H,P,SP,UP] THK Standard Linear Guide Accuracy and Preload Selectable HSR Series

Bearing No.  
HSR35A[1,2,3,4,5,6,7,8,9]+[123-3000/1]L[H,P,  
SP,UP]

HSR35A[1,2,3,4,5,6,7,8,9]+[123-30  
00/1]L[H,P,SP,UP] Bearing 2D drawings and 3D  
CAD models

Days to Ship	3 Days
Block Type	[Wide] A: Flanged w/Tapped Holes (Obsolete)
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	35
Rail Width W1	34 mm
Material	Carbon Steel
Mounting Height M	48 mm
Rail Length L	123 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	53900
Basic Load Rating Static Rating Co(N)	70200
Allowable Static Moment MA(N m)	895
Allowable Static Moment MB(N m)	895



## LY?MANUFACTURING CO.,LTD.

Allowable Static Moment MC(N m)	1050
Block external dimension W	100 mm
Block external dimension L	109.4 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M10
Mounting Hole Screw Depth	Through mm
Block dimension L1	80.4 mm