



LY?MANUFACTURING CO.,LTD.

5HR2042M+[93-1000/1]LM THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 5HR2042M+[93-1000/1]LM

Days to Ship	42 Days
Rail Width W1	15.6 mm
Mounting Height M	20 mm
Number of blocks	5
Material	Stainless Steel
Rail Length L	93 ~ 1000 mm
Accuracy Grade	Standard Grade
Callout Size	2042
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	9900
Basic Load Rating Static Rating Co(N)	17200
Allowable static moment MA(N · m)	308
Allowable static moment MB(N · m)	308
The outside dimension W of block	26.3 mm
The outside dimension L of block	91.6 mm
Mounting Hole Dimension S(M)	M6
The dimension L1 of bocks	56.6 mm
LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block	Not Provided

5HR2042M+[93-1000/1]LM Bearing 2D drawings and
3D CAD models



LY?MANUFACTURING CO.,LTD.

is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided